

Anti-Electrical Tracking Solution for Optical Core Routers



Overview

Ensuring the fire safety of high voltage (HV) outdoor insulators is key to maintain the reliable operation of the electrical grid. This requires the careful selection of suitable polymeric...

Key Takeaways

Using ADSS optical cables with anti-tracking polyethylene jackets and specialized additives prevents electrical tracking and dry band arcing in high-voltage environments.

Understanding Electrical Tracking in ADS

S CablesADSS (All-Dielectric Self-Supporting) optical cables are commonly installed on high-voltage transmission lines. In these environments, strong electric fields can induce surface potential differences on the cable, especially when the cable surface is wet or contaminated. This can lead to dry band arcing, which burns through the cable sheath, damages the aramid yarn, and eventually causes cable failure ().

Standard polyethylene jackets are insufficient for voltages above 12kV, making anti-tracking solutions essential.

Anti-



Tracking Sheath Materials

To mitigate electrical tracking, ADSS cables use tracking-resistant polyethylene sheath materials. Key strategies include:

- Additives for surface stability:** Incorporating trimethyl trifluoropropyl siloxane polymer elastomers enhances the thermostability and toughness of the polyethylene, improving resistance to electrical tracking ().
- Flame-retardant fillers:** Adding hibbsite (ATH) helps absorb heat generated by leakage currents, releasing water vapor to reduce surface temperature and prevent carbonization or dendritic corrosion ().

Optimized polymer base: High-density polyethylene (HDPE) or ethylene-vinyl acetate (EVA) are preferred, while polar polymers like PVC are avoided to maintain insulating properties ().

Reduced carbon black content: Limiting carbon black to below 2.6% prevents conductivity that could exacerbate tracking, while UV-resistant additives maintain long-term durability ().

Deployment Considerations

Voltage rating: Anti-tracking jackets are recommended for 110kV and 220kV lines, while standard PE jackets suffice for voltages below 12kV ().

Environmental factors: Ensure the cable surface remains clean and dry where possible, as contamination and moisture increase the risk of tracking.

Monitoring and testing: Optical Time Domain Reflectometry (OTDR) can be used to monitor insertion loss and detect early signs of sheath degradation in routed optical networks ().

Complementary Technologies

While the focus is on cable sheath materials, additional solutions like Smart Detect™ electronic markers can enhance asset management and monitoring of optical cables, though they primarily track location rather than prevent electrical tracking ().

Summary

For optical core routers deployed over high-voltage lines, ADSS cables with anti-tracking polyethylene jackets and specialized additives such as trimethyl trifluoropropyl siloxane and hibbsite provide the most effective protection against electrical tracking. Proper material selection, voltage-appropriate jackets, and environmental management are critical to ensure long-term reliability and safety of optical networking infrastructure ().

Article Content

Electrical tracking, erosion and flammability resistance of high ...

Ensuring the fire safety of high voltage (HV) outdoor insulators is key to maintain the reliable operation of the electrical grid. This requires the careful selection of suitable polymeric...

Anti-Tracking Cables: Reliable High-Voltage Solutions

Discover our Anti-Tracking Cables, designed to prevent electrical tracking and ensure safety and reliability in high-voltage applications.

Why ADSS Cables Fail on High-Voltage Towers:... | ABPTEL

Looking for the right optical hardware for your AI data center, GPU cluster, or FTTH project? ABPTEL ships from Shenzhen with OEM/ODM support, fast lead times, and engineering

CN102120839A

The anti-tracking polyethylene sheathing material has a favorable anti-tracking property and can eliminate the electrolytic corrosion phenomenon on the surface of an optical cable in a...

A Tracking-Resistance Test for ADSS-Type Optical Cables

Abstract Results are presented of an investigation of an ADSS optical cable for resistance to tracking. This cable is intended for a zonal communication line that is mounted on the supports of

EP1103986A1

A tracking resistant electrical insulating material or article suitable for medium to high voltage applications comprising a silane-modified polyolefin, and a heat-shrinkable article prepared...

Anti-Tracking ADSS Fiber Optic | Cable Manufacturer

The ABPTEL AT Jacket ADSS (Anti-Tracking Optical Cable) is purpose-built to mitigate this risk. It uses a specially formulated AT polymer outer sheath

TECHNICAL DATA SHEET

- Protection of electrical connections and terminations against electrical arcing.
- Reduction of the risk of electrical discharge in industrial and outdoor environments.

MarketsandMarkets

Revenue Impact Firm - MarketsandMarkets offers market research reports and quantified B2B research on 30000 high growth emerging opportunities to over 10000 clients worldwide. Get detailed insights

unsupervised_topic_modeling/topics/en/15/50/100/topics at ...

Contribute to annontopicmodel/unsupervised_topic_modeling development by creating an account on GitHub.

Why ADSS Cables Fail on High-Voltage Towers:... | ABPTCL

The Solution: AT Jacket (Anti-Tracking) You must determine the Space Potential at the hanging point on the tower. Below 12kV: Standard PE Jacket ADSS is safe and cost-effective. Above

Anti-Tracking Cables: Reliable High-Voltage Solutions

Our Anti-Tracking Cables are specially engineered to prevent electrical tracking, ensuring optimal performance and safety in high-voltage applications. These

Coherent routing: Enabling scalable and efficient IP-optical ...

Successful IP-optical integration requires more than plugging coherent optics in to router ports.

Electrical tracking, erosion and flammability resistance of high ...

During the initial phase of assessing electrical tracking and erosion in composite materials, researchers placed their focus on incorporating micron-sized fillers of different sizes.

NYT Connections archive

Every NYT Connections puzzle ever published is listed here, organised by date, with all four category groups and their sixteen words. The NYT only offers the current day's puzzle for free,

Electrical tracking, erosion and flammability resistance of high ...

This requires the careful selection of suitable polymeric composite materials with excellent electrical tracking, erosion, and fire resistance characteristics. To improve their performance against

Coherent optical interconnects using Fermat number transform

Siyu Chen, Zheli Liu and colleagues propose a holistic co-design optical communication scheme based on the self-homodyne coherent structure, anti-resonant hollow core fibre, and Fermat

Photonic Breakthroughs in Chip Design: A Survey of

This paper analyzes optical routers in Optical Networks-on-Chip (ONoC), focusing on MRRs, MZIs, and hybrid designs. It offers valuable insights

Contact Us

Continue your research online:

Website: <https://cgweb.co.za>

Technical inquiry: <https://cgweb.co.za/project-enquiry.html>

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

