Emission Shape of Multimode Fiber



Overview

Output beam shaping of a multimode fiber amplifierWe show numerically that the beam propagation factor M 2 of a single-frequency multimode fiber amplifier.

Key Takeaways

The emission shape of a multimode fiber is typically speckled and highly dependent on input conditions, fiber parameters, and mode interactions, often forming complex near-field and far-field intensity patterns.

Near-

Field and Far-Field PatternsThe near-field emission of a multimode fiber corresponds to the intensity distribution at the fiber end face. It is influenced by the number of guided modes, the input beam profile, and the alignment of the light source with the fiber core. For fibers with many modes, the near-field pattern often appears speckled due to interference between modes, and small changes in fiber bending, temperature, or launch conditions can significantly alter the pattern.

The far-field emission represents the angular distribution of light exiting the fiber. In multimode fibers, this can form conical or X-shaped patterns under nonlinear pulse propagation, especially for ultrashort pulses, due to intermodal frequency conversion and nonlinear effects. These patterns are sometimes referred to as discretized conical waves or X-waves, with off-axis tails emerging symmetrically around the central wavelength.

© 2026 CGWEB NETWORK INFRASTRUCTURE - All rights reserved

Factors Affecting Emission Shape

Input Beam Profile: Launching light entirely into the fundamental mode can produce a near single-mode output, but in practice, mode coupling often spreads power into higher-order modes, creating a speckled output. Fiber Parameters: Core diameter, numerical aperture, and length determine the number of supported modes and the resulting interference pattern. Nonlinear Effects: High-power pulses can induce nonlinear phenomena such as self-phase modulation and intermodal interactions, modifying the emission shape and producing conical or O-wave patterns.

Environmental Conditions: Bending, temperature variations, and stress can change the propagation constants of modes, affecting interference and beam quality.

Beam Shaping Techniques

To improve output beam quality, input or output beam shaping can be applied using spatial phase masks or wavefront control. This can reduce the beam propagation factor (M^2) and convert the naturally speckled output into a smoother, more collimated beam suitable for high-power applications. Multimode fibers are also used for beam homogenization, where polychromatic light averages out speckle patterns to produce a uniform intensity profile.

Applications

Understanding and controlling the emission shape is critical in applications such as: High-power laser delivery for material processing or medical procedures Imaging systems requiring multiple spatial modesOptical communications using mode-division multiplexing In summary, the emission shape of a multimode fiber is a complex function of input conditions, fiber design, and nonlinear interactions, ranging from speckled near-field patterns to structured far-field conical emissions, and can be actively shaped for improved beam quality.

Article Content

Output beam shaping of a multimode fiber amplifier

We show numerically that the beam propagation factor M 2 of a single-frequency multimode fiber amplifier can be reduced to nearly unity by shaping the input or output beam profile

Output beam shaping of a multimode fiber amplifier

The numerical results validate our approach of utilizing highly multimode excitation to mitigate nonlinear effects in high-power fiber amplifiers and performing input wavefront shaping to

Wavefront shaping enables high-power multimode fiber ...

© 2026 CGWEB NETWORK INFRASTRUCTURE - All rights reserved

Rothe et al. used a spatial wavefront-shaping technique for multimode fiber lasers that mitigates the detrimental processes, thus enabling output power to be increased appreciably while

Spatio-spectral light-by-light moulding in multimode fibre

Our approach opens new opportunities for supercontinuum generation in multimode fibres by exploiting the spatial overlap between high- and low-power multicolour beams.

Shaping the light amplified in a multimode fiber

We demonstrate that appropriate structuration of the input beam wavefront can shape the light amplified by a rare-earth-doped multimode fiber. Profiling of the wavefront was achieved by a...

(PDF) Wavefront shaping in multimode fibers by ...

Here, we demonstrate a potentially scalable route towards reconfigurable optical networks based on the use of a multimode fibre and advanced wavefront shaping techniques.

Discretized Conical Emission in Multimode Optical Fibers

In the case of multimode fibers, only a discrete number of guided modes is available and discrete conical emission is expected. The spectral position of the conical wave component in each

Shaping the light amplified in a multimode fiber

A technique that controls light propagation in rare earth-doped fiber optic cables makes it easier to peek inside disordered materials. Multimode optical fibers have large diametric cores that ...

Ultrafast Flat-Top Beam Emission with an All-Fiber Multimode Laser

The generation of pulsed flat-top beams using fiber lasers has gradually become a hot research topic in recent years. In this work, we propose an effective strategy to directly generate

Output beam shaping of a multimode fiber amplifier

The potential degradation of optical beam quality has been a major concern for highly multimode fiber amplifiers. We show numerically that the beam propagation factor M2 of a single

Multimode Fibers – optical glass fiber, large-core fibers, fiber ...

Multimode fibers are fibers supporting more than one guided mode per polarization direction – in some cases even a large number of modes.

© 2026 CGWEB NETWORK INFRASTRUCTURE - All rights reserved

Multi-mode optical fiber

Multi-mode optical fiber is a type of optical fiber mostly used for communication over short distances, such as within a building or on a campus. Multi-mode links can be used for data rates up to 800 Gbit/s.

Space-time wave packets in multimode optical fibers with ...

Su et al. demonstrate ultra-fast light pulses in multimode fiber with dynamically evolving spatial profiles and tunable group velocities ranging from subluminal to superluminal and negative

Mitigating stimulated Brillouin scattering in multimode fibers with ...

The authors demonstrate a high-power delivery through a highly multimode optical fiber by shaping the incident wavefront of a laser beam to strongly suppress the stimulated Brillouin

Multimode nonlinear fiber optics, a spatiotemporal avenue

It clearly appears that multimode fibers with transverse and longitudinal microstructuration can open a new way for high power single mode

Multimode Beams – free space, waveguide, fiber, monochromatic ...

Multimode beams cannot be transmitted through single-mode fibers. Most fiber amplifiers can amplify only single-mode or few-mode light. One can also make fiber amplifiers for highly multimode

Multimode Fiber

In practice, multimode fiber suffers from random linear coupling among its modes because of manufacturing variations in the shape and size of the fiber''s core along its length [170–173].

Simulation and measurement of radiation loss at multimode fiber ...

The emission pattern of the radiated light has been calculated and qualitative agreement with the measured pattern found. It is suspected that the differences between simulation and experiment

© 2026 CGWEB NETWORK INFRASTRUCTURE - All rights reserved

Contact Us

Continue your research online:

Website: https://cgweb.co.za
Technical inquiry: https://cgweb.co.za/project-enquiry.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 CGWEB NETWORK INFRASTRUCTURE - All rights reserved