How long is the cable tray jumper

Overview

Cable Tray Jumper, (2) 3/8" Holes, 1" Spacing, 6" LengthThe Cable Tray Jumper allows for flexible cable routing around obstacles and transitions, maintaini.

Key Takeaways

Cable tray jumpers are used to electrically bond and connect sections of cable tray, with standard lengths typically ranging from 6 inches to 36 inches depending on the application.

Standard Specifications

Length: Standard Snap Track bonding jumpers are 36 inches long, designed to span discontinuities in expansion splices and adjustable fittings, though optional lengths are available upon request. Smaller jumpers, such as those with 6-inch lengths, are also used for shorter connections or specific routing needs. Material: Jumpers are typically made from durable conductive metals to ensure reliable grounding and electrical continuity.

Aluminum and copper are common materials, with some products rated for high current applications (e.g., 2000 Amp aluminum bonding jumpers),. Hole Configuration: Many jumpers feature pre-drilled holes for mounting. For example, a 6-inch jumper may have two 3/8-inch holes spaced 1 inch apart to facilitate secure attachment to the cable tray.



© 2026 CGWEB NETWORK INFRASTRUCTURE - All rights reserved

Color Coding: Standard bonding jumpers are often green, indicating grounding, though other colors may be available upon request. Installation: Jumpers are installed to maintain electrical continuity across tray sections, especially at expansion joints, fittings, or transitions. Proper installation ensures effective grounding and reduces the risk of electrical hazards.

Considerations

Length Selection: Choose jumper length based on the distance between tray sections and the type of fitting or splice. Longer jumpers are used for expansion joints, while shorter jumpers are suitable for direct connections. Compliance: Ensure that the jumper meets relevant electrical codes and standards for grounding and bonding in your region.

UL-listed or CE-marked products are recommended for safety and compliance. Flexibility: Some jumpers are designed to allow flexible routing around obstacles while maintaining a clean cable pathway. By selecting the appropriate length, material, and hole configuration, cable tray jumpers provide reliable electrical bonding and maintain organized cable management across installations.

Article Content

Cable Tray Jumper, (2) 3/8" Holes, 1" Spacing, 6" Length

The Cable Tray Jumper allows for flexible cable routing around obstacles and transitions, maintaining a clean and organized pathway.

Tuling Cable Tray Earthing Jumper

At Tuling, you can also optimize the jumper length according to your applications. Generally, the cable tray earthing jumpers are 12″ to 120″ in length. Our earthing jumpers for the cable tray are made of a

Cable Tray Bonding Jumpers

Ground Strap Kit, 8.75" Long, Tin Plated Copper Wire. Includes Cable with Crimped Lugs & Hardware

PW Ladder Cable Tray Bonding Jumper

INSTALLATION INSTRUCTIONS: SET PROPER EXPANSION GAP BETWEEN CABLE TRAY ENDS PER NEMA VE-2 POSITION END OF BONDING JUMPER 9-5/8" FROM EACH CABLE TRAY END

Harger, Inc.

HARGER''s WS-CTJUMP9 cable tray jumper cable. Features 1/4 in 2 hole lug and #6 THW wire. 9 in of wire. 15 in overall length.

© 2026 CGWEB NETWORK INFRASTRUCTURE - All rights reserved

FBD16-1 | ABB

Bonding Jumper, One Braid. 16 Inch Long x 1 inch wide x .2 inch Thick, Pads 1 inch wide x 1.3 inch long, (1) 0.438 inch Diameter Hole each side. Circular Mil Area 76,800. CSA and UL Certified.

Are Bonding Jumpers Required for Standard Cable Tray Splice Plates?

Whether you need extra wires (jumpers) depends on if your connecting plates are tested for grounding. If the plates are UL Classified, they are strong enough to carry electricity safely by

Cable Tray Grounding Jumper and Bonding Jumper -

Send us your drawings, samples, or cable tray installation requirements, and our team will check the design and prepare a quotation for your cable tray grounding jumper project.

I-BEAM Ladder Bonding Jumper [GBJ-C]

Our aluminum, I-beam ladder cable trays feature 3-inch tangents and are using connectable with our fittings and accessories. Aluminum ladder cable trays benefit from being lightweight and resistant to

Server Room Cable Tray Guide: Best Types, Sizing

Designing a server room? Learn how to choose the right cable tray, size it correctly, and avoid costly mistakes. Expert tips on airflow, layout, and

How to Choose Cable Tray for High Voltage System

Selecting a cable tray for high voltage power cables is a critical engineering decision that directly impacts system safety, thermal performance,

FRP Cable Tray: Benefits, Uses, and Buying Tips

Learn how to choose the right FRP cable tray for industrial projects, with tips on load, corrosion resistance, customization, and long-term value.

How Long Should Jumper Cables Be?

Choosing jumper cable length means balancing reach and power. Learn how gauge, vehicle type, and battery location affect the ideal size.

NEC Article 392 Requirements for Cable Tray Systems

NEC Article 392 sets the rules for cable tray systems, from permitted wiring methods and installation requirements to cable fill and ampacity adjustments.

What Is MPO/MTP Trunk Cable? Data Center Backbone Complete

© 2026 CGWEB NETWORK INFRASTRUCTURE - All rights reserved

Complete 2026 guide to MPO/MTP trunk cables. Learn definitions, polarity, types, UPC/APC differences, deployment rules, and selection tips for modern 40G/100G/400G/800G data center backbones.

Cable Tray Installation Guidelines for Engineers

All cable tray systems shall be bonded together with bonding jumpers. Cable trays shall be grounded at least every 15 m (50 ft) and at both ends for Cable Tray Installation Guidelines for Engineers.

unsupervised_topic_modeling/topics/en/15/100/100/topics at ...

Contribute to annontopicmodel/unsupervised_topic_modeling development by creating an account on GitHub.

How to Properly Replace a Car Battery

Baking soda and water mixture: For neutralizing any spilled acid. Jumper cables (optional, but recommended): To maintain electronic memory. A battery carrier (optional): To make lifting the

Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

Contact Us

Continue your research online:

Website: https://cgweb.co.za
Technical inquiry: https://cgweb.co.za/project-enquiry.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 CGWEB NETWORK INFRASTRUCTURE - All rights reserved