How thick is a 216-core optical cable



Overview

An In-Depth Guide to 216 Core Optic Fiber Cable: Standards, Grades, Each fiber in a tight-buffered 216-core cable is coated with a thick protective plastic.

Key Takeaways

A 216-core optical fiber cable typically has an outer diameter ranging from approximately 25 mm to 40 mm, depending on construction type and armoring.


Cable Construction and Diameter Factors

The overall thickness of a 216-core fiber optic cable depends on several design factors: Fiber Type and Coating: Each fiber is usually coated with a 900 µm protective layer in tight-buffered designs, which adds to the cable diameter.

Loose-

Tube vs Tight-Buffered: Loose-tube cables house fibers in gel-filled or dry-block tubes, allowing movement and thermal expansion. These tubes, along with the central strength member, increase the cable diameter. Armoring: Armored cables include a metallic (corrugated steel) or non-metallic (aramid) layer beneath the outer jacket, which can add several millimeters to the overall thickness.

Outer Sheath: The protective outer jacket, often made of polyethylene or similar durable material, contributes to the final diameter and provides environmental protection.



© 2026 CGWEB NETWORK INFRASTRUCTURE - All rights reserved

Typical Diameter Ranges

Indoor, tight-buffered 216-core cables: Approximately 25–30 mm in diameter, suitable for data centers and patch panels. Outdoor, loose-tube 216-core cables: Approximately 30–40 mm, depending on the number of loose tubes, gel or dry-block filling, and armoring. Armored, direct-burial cables: Can reach 35–40 mm or slightly more, due to the added mechanical protection layers.

Summary

A 216-core optical fiber cable is a high-density solution designed for telecom backbones, data centers, and enterprise networks. Its outer diameter typically ranges from 25 mm to 40 mm, influenced by fiber coating, tube design, armoring, and outer jacket materials. When planning installation, it is important to consult the specific manufacturer's datasheet for exact dimensions, as variations exist between tight-buffered, loose-tube, and armored designs.

Article Content

An In-Depth Guide to 216 Core Optic Fiber Cable: Standards, Grades,

Each fiber in a tight-buffered 216-core cable is coated with a thick protective plastic layer (typically 900µm), enhancing durability and flexibility. This design simplifies handling and termination without

Product Spec Sheet 216FUC-T4101D20

These cables also provide high-fiber density within a given cable diameter while allowing flexibility to suit many system configurations. The single armored construction provides additional

Multi-Loose Tube Fiber Cable

Universal (Indoor/Outdoor) dry core optical fiber Multi Loose Tube cable with aramid yarns as strength member and Low Smoke Zero Halogen outer jacket. Existing out of 12 tubes with a diameter of

FS1L216ND Technical Data Sheet

Product Description Loose Tube Fiber Cable, Outdoor, OM1, Multimode, 216 Fibers, 12 Fibers per Tube Dry, Black Jacket

Fiber Optic Cable Size Chart: Complete Guide

Fiber optic cable size chart with complete guide to core, cladding, and jacket dimensions, types, and specifications for networking and installation use.

216 Count Fiber Optic Cables

© 2026 CGWEB NETWORK INFRASTRUCTURE - All rights reserved

We stock a full array of multimode fiber cable and singlemode fiber optic cables in loose tube, indoor, indoor outdoor, plenum, breakout, tight buffer, 10 Gigabit Aqua fiber optic cable and more.

TECHNICAL DATA SHEET

TECHNICAL DATA SHEET CABLE CONSTRUCTION SM-MLT-SA-SJ 216FO 216 CORES BURIED & DUCT TYPE SINGLE MODE FIBER OPTIC CABLES with SINGLE JACKET and STEEL ARMOR ...

AFL Global 216-Fiber Loose Tube 50/125um Multimode Outdoor Cable

Non-armored loose tube cable designed with 216 fibers, 18w tubes and 12 fibers (no fillers). Provides high fiber counts with the flexibility and versatility required for demanding installations.

216 Fiber 12 Strand 27 Series Riser Gel Filled Loose

This document establishes the specification requirements for a riser rated

64624447-216 | O-216-LD-8M-M12BL/20G/PE/PA

64624447-216 | O-216-LD-8M-M12BL/20G/PE/PA Base Product: O-LD Available in: Australia/New Zealand Outdoor Fiber Cable, 216-fiber, singlemode OS2, loose tube, blue Buy from a Distributor

F_216-312___LTNG

This loose tube dielectric optical cable is designed for external underground installations in ducts or by direct burial. GRP armour provides rodent protection and polyamide provides anti-termite protection.

AFL Global 216-Fiber Loose Tube 50/125um Multimode Outdoor Cable

Non-Armored loose tube optic cable provides high-fiber counts with its versatility. Fiber Count: 216. Tubes/Fibers: 18w/12 (no fillers). Request a quote.

216TUA-T4131D20 | ALTOS® Figure-8 Loose Tube, Gel-Free Cable 216

Corning ALTOS® figure-8 gel-free cables are self-supporting aerial cables designed for easy and economical one-step installation. The loose tube design provides stable performance over a wide

216 Core Outdoor Stranded Loose Tube Fiber Optical Cable

Hongan optical fiber cable company has always stood on high starting point, high technology and high standard since it was founded. Production capacity is 50 million core kilometers. Respectively

FIBER OPTIC CABLE Product Specifications

© 2026 CGWEB NETWORK INFRASTRUCTURE - All rights reserved

Cable Core: The sub-units and conductors are stranded around the CSM, using reverse oscillation. Overall Sheath: UV resistant black flame retardant Polyvinyl Chloride pcord applied under the overall

MPP Vertical Optical Fiber Splice Box Dia 230x440mm 96 Cores 11

There are 11 circular cable ports, the bigger port can be used for cable loop through. Stacked structure splice tray and independent insulation grounding device make the optical fiber core configuration,

Multi-Loose Tube Fiber Cable

Outdoor dry core optical fiber Multi Loose Tube cable with aramid yarns as strength member, polyethylene inner jacket, Corrugated Steel Tape (Full Rodent Protected) armor and polyethylene

FS3H216NG Technical Data Sheet

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages

Contact Us

Continue your research online:

Website: https://cgweb.co.za
Technical inquiry: https://cgweb.co.za/project-enquiry.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 CGWEB NETWORK INFRASTRUCTURE - All rights reserved