Nepal OEM Single-Fiber Bidirectional NRZ



Overview

Using Bi-Directional (BIDI) transmission technology, this module transmits and receives data over one single mode fiber strand, helping reduce fiber usage and deployment cost.

Key Takeaways

Single-fiber bidirectional NRZ devices in Nepal enable long-distance, high-speed optical transmission over a single fiber using NRZ modulation, with local suppliers offering SFP+ transceivers and MUX/DEMUX boards. OverviewSingle-fiber bidirectional (BiDi) NRZ technology allows simultaneous transmission and reception of optical signals over a single fiber, reducing fiber infrastructure costs while maintaining high-speed communication.

NR

Z (Non-Return-to-Zero) modulation is commonly used for 10G and higher data rates, providing efficient and reliable signal encoding.

Key Products in Nepal10

G Bi



© 2026 CGWEB NETWORK INFRASTRUCTURE - All rights reserved

Di SFP+ TransceiversSupport transmission distances from 10 km to 100 kmUse a single LC optical interfaceFeatures include low power consumption, compact size, high reliability, and wide temperature rangeCommonly used in SDH/SONET and Ethernet networksAvailable from suppliers like Adhistore Pvt. Ltd. in Nepal Single-Fiber Fixed MUX/DEMUX Boards (SBM)Designed for DWDM networks with multiple wavelengthsCan multiplex different wavelengths onto one fiber or demultiplex multiple channelsBased on thin film filter (TFF) technology and compatible with ITU grid 100 GHz channel spacingSupports serial connection of EDFA for long-distance bidirectional transmissionIncludes built-in OSC monitoring channel for network managementOffered by D Tech Trading and available through distributors like Eman Communications ApplicationsTelecommunication networks: ISPs and cable operators use BiDi NRZ devices to optimize fiber usage.

DWD

M systems: Multiplexing multiple wavelengths on a single fiber for high-capacity links. Long-distance transmission: Supports distances up to 100 km with proper amplification. Network monitoring: OSC channels allow real-time performance tracking.

Suppliers in Nepal

Adhistore Pvt. Ltd.: Offers 10G BiDi SFP+ transceivers Technovate International Pvt. Ltd.: Provides end-to-end fiber optic solutions and telecommunication equipment D Tech Trading / Eman Communications: Supplies SBM MUX/DEMUX boards for DWDM applications Cable Tech Nepal: Offers fiber optic cables compatible with BiDi systems These products are suitable for network operators, ISPs, and enterprises looking to deploy cost-effective, high-speed optical links using single-fiber bidirectional NRZ technology.

Article Content

100G QSFP28 ER4 60KM LC Optical Transceiver (EML)

A4: Yes, we offer OEM/ODM services including custom labeling, firmware, and compatibility testing. Q5: How does 100G QSFP28 BiDi reduce fiber costs? A5: BiDi modules enable bidirectional 100G

SFP 100G BIDI QSFP28 LR1-20KmSFP 100G BIDI

Featuring PAM4 modulation, QSFP28 MSA compliance, simplex LC connector, and support for transmission distances up to 10KM / 20KM over single-mode fiber,

SFP 10G, BIDI Tx1550nm/Rx1490nm, 80KM, LC DDM in nepal

© 2026 CGWEB NETWORK INFRASTRUCTURE - All rights reserved

Using Bi-Directional (BIDI) transmission technology, this module transmits and receives data over one single mode fiber strand, helping reduce fiber usage and deployment cost. It supports transmission

Shopping

Based on thin film filter (TFF) technology, it works on ITU grid with 100GHz channel spacing. The wavelength of the ITU channel is optional. It supports serial

The Essential Guide to BiDi Transceivers: Everything You Need to Know

BiDi transceiver, a compact optical transceiver with WDM (wavelength division multiplexing) technology and SFP multi-source protocol (MSA) compliance, allows fast data

The Complete Guide to BiDi Transceiver

BiDi technology optimizes bidirectional data transmission on a single fiber, thereby improving network efficiency, and it has demonstrated success across diverse industries,

Wholesale Fiber Optic SFP 1G to 100G In Nepal

Wholesalers & Direct Importers of Fiber Optic SFP of Various Types: 1.25 G SFP Module, 1.25G Bisdi SFP, 1.25G CWDM SFP, 1.25G DWDM SFP,155m

BiDi SFP+

The 10G BIDI single fiber bidirectional SFP+ series optical transceiver support a variety of transmission distances from 10km to 100km. The series of products

100G QSFP28 BiDi : Optical Transceiver Module | NEC

NEC''s 100G QSFP28 BiDi optical transceiver enables the transmission and reception of 100Gb/s high-speed data over a single optical fiber. By enabling bidirectional transmission over a single fiber, this

Shopping

BiDi (bidirectional): This means the transceiver is capable of both transmitting and receiving data over a single fiber optic strand. It utilizes two different wavelengths for transmission and reception: 1550

A Comparison of Single-Ended, NRZ Unidirectional Signaling and Single ...

This article compares single-ended, NRZ unidirectional (UD) signaling to single-ended, NRZ simultaneous bidirectional signaling for ultrashort-reach (USR) die-to-die (D2D) links in terms of

Single Fiber vs Dual Fiber Transceivers Understanding

© 2026 CGWEB NETWORK INFRASTRUCTURE - All rights reserved

Single fiber transceivers, like the Bidi Transceiver, use one fiber for bidirectional data, while dual fiber transceivers require two fibers for separate TX

University of Toronto

D. Jarrett-Amor and T.C. Carusone, "A Comparison Between Single-Ended, NRZ Unidirectional Signaling and Single-Ended, NRZ Simultaneous-Bidirectional Signaling for Die-to-Die Links," in IEEE

What is the Difference Between SFP and BiDi SFP? Your Ultimate Guide

Compare SFP vs BiDi SFP: key differences, fiber requirements, compatibility, and best use cases to help you choose the right SFP module for your network.

A Comparison Between Single-Ended, NRZ Unidirectional ...

A Comparison Between Single-Ended, NRZ Unidirectional Signaling and Single-Ended, NRZ Simultaneous-Bidirectional Signaling for Die-to-Die Links ieeexplore.ieee 148 2 Comments

Power and data simultaneous transmission using double-clad fibers ...

DCFs offer distinct advantages over other fiber types due to their unique design, which enables simultaneous transmission of data and power over a single fiber.

Pair of 10G SFP+ Bidi Transceiver, 10GBase-BIDI Nepal | Ubuy

10GBASE-BIDI Bidirectional SFP+ to single LC Optical transceiver module, Single Mode, Wave length: Up: TX1270nm/RX1330nm; Down: TX1330nm/RX1270nm, DDM, up to 10km over single LC.

(PDF) Characterization of Standard Single-Mode Fiber Link for a NRZ ...

Characterization of Standard Single-Mode Fiber Link for a NRZ Modulated Optical Signal at 40 Gbps by Ashvini Ganesh Canjeevaram B.E. (Hons) (Electrical and Electronics), Birla Institute of Technology

© 2026 CGWEB NETWORK INFRASTRUCTURE - All rights reserved

Contact Us

Continue your research online:

Website: https://cgweb.co.za
Technical inquiry: https://cgweb.co.za/project-enquiry.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 CGWEB NETWORK INFRASTRUCTURE - All rights reserved