

Optocoupler DC Relay Module

Length:14.5mm
Small-end inner diameter:2.0mm
Large-end inner diameter:3.5mm
Outer diameter:5.2mm



Overview

The 2 Channel 5V 10A Relay Module with Optocoupler is a versatile electronic component designed to control high-voltage devices using low-voltage signals. It features two independent relay channels, each capable of handling up to 10A at 250V AC or 30V DC. They're perfectly suited for industrial automation, process and power engineering, rail systems, shipbuilding, and control cabinet manufacturing. Additionally, there is a jumper-based. In the following post I have explained how to drive a relay by using an isolated method, or through an optocoupler device. We will learn three methods, first method is by connecting relay directly with the optocoupler output pins, second method is by using external PNP transistors, and third method. ELEGOO Relay Module with Optocoupler for Arduino?

UNO R3 MEGA 2560 1280 DSP ARM PIC AVR STM32 Raspberry Pi – ELEGOO US Shipping calculated at checkout. Orders placed on ELEGOO US (us. com) can be shipped to the United States. Pre-orders will ship by the estimated date listed on the product. PLC-INTERFACE, consisting of DIN rail-mountable basic terminal block with screw connection and plug-in miniature solid-state relay, input: 24 V DC, output: 3.

Article Content

5V 2/4/8 Channel Relay Modules with Optocoupler User's Guide

Simply supply the module with 5V DC and GND through the terminals below. Additionally, connect the 5V active low input pins (Optocoupler circuit inputs) to your Arduino ports to

How to Connect a Relay through an Opto-Coupler

The following concepts show how a relay driver can be configured with an optocoupler using transistors. As shown in the following circuit diagrams, the relay driver may consist a NPN transistor or a PNP

Relay Module with Optocoupler (8 Channel/4 Channel

With a relay coil to absorb the diode protection. Standard interface that can be controlled directly by microcontroller (Arduino?, 8051, AVR, PIC, DSP, ARM,

Amazon : SunFounder 2 Channel DC 5V Relay

It is equipped with high-current relays that work under AC250V 10A or DC30V 10A. It has a standard interface that can be controlled directly by microcontroller.

How to Use Relay with optocoupler: Examples, Pinouts,

Learn how to use the Relay with optocoupler with detailed documentation, including pinouts, usage guides, and example projects. Perfect for students, hobbyists,

Appoldt GmbH Herstellung und Vertrieb

2.05 SSR - DC/DC < 24A (sensitiv) TS35/DIN-RAIL [912 KB] 2.06 SSR - DC/DC < 20A auf Sockel TS35 /DIN-RAIL [117 KB] 2.07 SSR - DC/DC < 5A Sockel 1-4-8 STECK/PLUG [171 ...

Relay module (857-304) | WAGO

Relay module; Nominal input voltage: 24 VDC; 1 changeover contact; Limiting continuous current: 6 A; Yellow status indicator; Module width: 6 mm; gray 1 of 4 DC load limit curve Color:

Industrial isolated 8-Channel ESP32-S3 WiFi Relay Module RS485

ESP32-S3-ETH-8DI-8RO is an industrial-grade 8-channel WiFi network relay based on ESP32-S3 main controller and supports WiFi, Bluetooth, RS485, network port and other peripheral interfaces. It has

NOYITO 4-Channel Relay Module with Optocoupler Isolation, 30A

Optocoupler Isolation Each channel is isolated with an optocoupler to reduce interference from the control circuit. **High Current Capacity** The module uses high-power relays rated for up to 30A at DC

6-Channel 5V Relay Module with Optocoupler | Manualsee

Features Opto-Isolated Inputs Each relay channel has an optocoupler for electrical isolation between the control circuit and the relay, reducing interference and improving stability. **High/Low Level Trigger**

KKmoon Relay Module AC 250V 10A Optocoupler Isolation Relays Modules ...

Maximum Load: The relay module adopts genuine relay, the maximum load of normally open interface, AC 250V 10A, DC 30V 10A **Strong Drive:** Relay module adopts SMD optocoupler isolation, with

NOYITO 6-Channel Relay Module with Optocoupler Isolation

Overview This relay module provides 6 individually controllable channels for switching AC or DC loads. It features optocoupler isolation for signal separation and supports high or low level trigger selection

High and Low Level Trigger Relay Control Module with Optocoupler ...

Specifications: Part name: relay module Material: PCB circuit board Color: as shown Power supply voltage: 5V, 12V, 24V (optional) Size: 14.2x5cm/5.59x1.97inch *Power supply voltage: 5V Quiescent

2 Channel Relay Module with Isolated Optocoupler

This relay module is designed for switching loads using a 12V DC control signal. It features two independent relay channels with optocoupler isolation for signal separation.

38-3D 16 Channel Relay Module

5V 16-Channel Relay Module with Optocoupler Isolation (High/Low Level Trigger) This 5V 16-channel relay module uses SMD optocoupler isolation to provide stable performance and reliable driving

Relay Shield Module, 4 Channel 5V Relay • £7.90

5V 4 Channel relay output modules, relay output contacts up to 250A 10A. With optocoupler. Standard interface, can be extended on various development boards. Be able to control various appliances,

8-36V 8-CHANNEL TIME Delay Relay Interface Board Module Optocoupler

8-36V 8-CHANNEL TIME Delay Relay Interface Board Module Optocoupler LED SG - £26.28. FOR SALE! Trigger signal input supports user selection, high level or low level 137491234906

URJIX™ 5V Relay Module with Optocoupler 4 Channel Relay Module

5V 4 Channel Relay Output Modules, Relay Output Contacts Up To 250A 10A. With Optocoupler. Standard Interface, Can Be Extended On Various Development Boards. Be Able To Control Various

Contact Us

Continue your research online:

Website: <https://cgweb.co.za>

Technical inquiry: <https://cgweb.co.za/project-enquiry.html>

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

