Which end of the optical module 1270 starts with



Overview

Using 1270nm at the transmit end and 1330nm at the receive end, the SFP+ BR40U provides 10Gb/s throughput over single-mode fiber (SMF) with a transmission distance of up to 40km. The electrical interface is an MSA-compliant 20-pin edge connector and the optical interface is a. The CWDM-SFP10G-40S series optical transceiver is designed for fiber communications application such as 10G Ethernet, which fully compliant with the specification of SFP+ MSA SFF-8431. There are. Optcore's OPC10G-xx40DCR is a high performance and cost-effective 10Gb/s CWDM (Coarse Wavelength-Division Multiplexing) SFP+ ER transceiver module, which provides a high capacity, high bandwidth communication solutions for multiplexed optical networks. 3Gbps Small Form Factor Pluggable SFP+ BIDI module for 10GBASE Ethernet. The module can be used with any network device that accepts standard MSA transceivers - e. D-Link, Zyxel, Mikrotik and Ubiquity among others. This is the Tx1270/Rx1330 (upstream) half of the matched 10GBASE-BX20 pair, deployed against a Tx1330/Rx1270.



© 2026 CGWEB NETWORK INFRASTRUCTURE - All rights reserved

Article Content

10Gb/s CWDM 1270-1450nm SFP+ ER Transceiver Module

This CWDM SFP+ ER transceiver module is designed for 10 Gigabit Ethernet links up to 40km over single-mode fiber. It features a highly reliable CWDM DFB transmitter and PIN photo-detector into

Cisco CWDM-SFP10G-1270 10G CWDM SFP+ Transceiver Module

High Capacity CWDM Transmission CWDM modules, along with MUX/DEMUX devices, improve fiber optic network capacity and efficiency, enabling flexible wavelength adjustment and simplify network

10GBASE-BR BIDI SFP+ 1270/1330nm – High-Speed Long Reach

Using 1270nm at the transmit end and 1330nm at the receive end, the SFP+ BR40U provides 10Gb/s throughput over single-mode fiber (SMF) with a transmission distance of up to 40km.

7818479 | Optical Demultiplexer, 18 channels

7818479 | Optical Demultiplexer, 18 channels Available in: Asia Australia/New Zealand EMEA Latin America North America CWDM Fiber Optical Module, Demux, 1270-1610 nm, LC/PC, 18 channels

1.25G CWDM SFP module, 1270nm (CH27), 80km over SMF, DDM, du

The module can be used with any network device that accepts standard MSA transceivers - e.g. D-Link, Zyxel, Mikrotik and Ubiquity among others. In case you need the transceiver with specific coding for

10G BiDi SFP+ 20km Tx1270/Rx1330 | €16.33 | EDGE Optical Solutions

10GBASE-BX20 10G BiDi SFP+, 20km single fiber, Tx1270/Rx1330nm, 9dB budget, DOM. Matched-pair module. EU stock + lifetime warranty. €16.33.

SFP-XG-TX1270-RX1330-IN

SFP-XG-TX1270/RX1330-IN 10 Gigabit Single-Mode 20km BIDI Optical Module-TX1270/RX1330 Specification Download How to buy

ATGBICS SFP-GE-LX-SM1270-BIDI-C network transceiver module

Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product is built to the exact specification of Huawei SFP-GE-LX

10G BiDi SFP+ 40km | Tx1270/Rx1330 | Single Fiber Compatible

© 2026 CGWEB NETWORK INFRASTRUCTURE - All rights reserved

Our 10G BiDi SFP+ 40km transceiver delivers extended single-fiber reach with Tx1270nm/Rx1330nm wavelength technology. Providing robust 16 dB link budget over 40km single-mode fiber, this 10G

Cisco CWDM-SFP10G-1270 10G CWDM SFP+

Check FS 10gbe CWDM SFP+ transceiver module Compatible Cisco CWDM-SFP10G-1270 datasheet (SMF, 1270nm, 40km, LC connector) and price list.

Fiber Optic Multi-Channel Optical PON Power Meter (1270

Description The L-com FOTM-OPM-MCH Multi-channel Power Meter, optimized for PON (Passive Optical Networking) Applications. The L-com FOTM-OPM-MCH features Six (6) wavelengths,

TJ1270_HD

An optical fiber connector terminates the end of an optical fiber, and enables quicker connection and disconnection than splicing. The connectors mechanically couple and align the cores of fibers so that

10G CWDM Single-Mode Optical Module

SFP+ transceiver for CWDM that supports 10G connections up to 20 km using single-mode fiber with a duplex LC UPC connector.

25G SFP28 CWDM 1270-1330 40km DDM Transceiver

The 25G CWDM SFP28 is widely used in 25G Ethernet and 5G front haul CPRI/eCPRI, with a transmission distance of up to 10km or 15km through a pair of single-mode optical fibers. 25g sfp28

10G BIDI SFP+ 1330nm-TX/1270nm-RX 10km Transceiver Datasheet

The host uses SDA in conjunction with SCL to mark the start and end of serial protocol activation. The memories are organized as a series of 8-bit data words that can be addressed individually or

Hanutech 60KM 10G Bidi SFP+ Single Mode Single

Hanutech 60KM 10G Bidi SFP+ Single Mode Single Fiber LC Optical SFP Module, LR Bidi Transceiver 1270/1330nm Data Transmission 60KM : Amazon :

Understanding Fiber Optics – Your Quick Guide to SFP

Understanding Fiber Optics – Your Quick Guide to SFP Transceivers What is an SFP Transceiver? SFP (small form-factor pluggable) is a compact, hot-pluggable

Hanutech 10G Single Mode SFP+ Bidi Modules 40KM Fiber Optic

© 2026 CGWEB NETWORK INFRASTRUCTURE - All rights reserved

Hanutech 10G Single Mode SFP+ Bidi Modules 40KM Fiber Optic Transceivers 1270/1330nm, LC Fiber Interface- 1 Year Warranty

Contact Us

Continue your research online:

Website: https://cgweb.co.za
Technical inquiry: https://cgweb.co.za/project-enquiry.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 CGWEB NETWORK INFRASTRUCTURE - All rights reserved